



10" Ranch Axe Tree Shears

for Skid Steer Loaders

Photo Below: Base Model
10" Ranch Axe



Photo: 10" Ranch Axe Tree Shear shown with optional pushbar. The pushbar allows operators to direct sheared tree.

-
- The **Dymax 10" Ranch Axe Tree Shears** for skid steer loaders are ideal for general land clearing where materials are less than 254mm in diameter.
 - **Dymax 10" Ranch Axe Tree Shears** feature near-ground level cutting, eliminating stump problems and leaving the terrain smooth.
 - The **Dymax 10" Ranch Axe Tree Shear** is designed for machines with a minimum of 550kg of operating capacity, minimum flow rate of 56 lpm.
 - Shearing cylinder is rated at 20700 kPa and optimum results will be obtained near those levels. Do not exceed 22080 kPa.
 - Hydraulic or manual rotating models are available. Optional pushbars and brushguards are also available.
 - All units are equipped with universal mount skid steer coupler hooks to work with most new model skid steer loaders.
- Contact **Practicality Brown Ltd. UK Distributor for more information**
- **Tel: 01295 690011**

10" Ranch Axe Tree Shears



Dymax 10" Ranch Axe Tree Shears are available in manual or hydraulic rotating models. Hydraulic rotating models are setup with a electro/hydraulic diverter valve.



Specifications

Cylinder	Number	Rod (mm)	Bore (mm)	Stroke (mm)
Shear	1	50.8	101.6	304.8

Specifications and Dimensions	Ranch Axe Tree Shear (Base Model)	Ranch Axe Tree Shear (Pushbar Model)
Weight (kilograms)	326 kg	394 kg
Height (mm)	584.0 mm	863.0 mm
Width at shear arms (mm)	1536.0 mm	1536.0 mm
Overall depth (mm)	1168.0 mm	1168.0 mm
Shear blade material	12.7mm T1 milled knife edge	12.7mm T1 milled knife edge
Hydraulics (Liters/Minute) (KPA)	56.00 LPM (minimum) 20700 kPa (maximum)	56.00 LPM (minimum) 20700 kPa (maximum)

Materials and specifications subject to change without notice.



Practicality Brown Ltd, Iver Stud, Iver, Bucks SL0 9LA United Kingdom
Tel: 01295 690011 www.treeshears.co.uk sales@treeshears.co.uk

Form No. 1186UK (9-06)